

Multiple Diameters

Eco-friendly



**Multiple
Beam Spreads**

Compact

Adjustable Axis

Low Voltage

61 Month Warranty



Description

The TR-100 Tree Ring is manufactured with powder coated stainless steel frame for long durability.

LED technology delivers a reliable, low maintenance, high performance and energy efficient lighting choice.

Engineered specifically for LED technology, the design of the TR-100, in combination with our AXIS-TIC, provides critical thermal transfer and heat removal.

Other features include anti-wicking power lead, tool-free optic interchange and service upgrade capability.

TR-100 LED TREE RING




Specifications

Light Source	High-brightness LED (light emitting diode)
LED Life (L70)	50,000 hours average*
Input Voltage	11 to 15 VAC/VDC
Power Consumption	10 Watts per fixture
Color Temperature	3000 or 4000k
CRI	80 Typical
Optic	Interchangeable TIR Lens
Material	6061-T6 Aluminum / SS
Fasteners	Stainless steel hardware
Operating Temperature	-31F to 122F (-35C to 50C)
Listings	Lights are ETL listed to UL Standards 8750 and 1836 CSA C22.2 No. 250.7-07




*LED life is defined as the time to 70% lumen maintenance (L70)

Brightness



Ordering Guide



THE LED COMPANY

160 McCormick Ave, Costa Mesa, CA 92626

Phone: 714.862.2920
 Fax: 714.492.1008
 Email: sales@ledcohome.com
 Web: www.ledcohome.com

Manufactured in the USA