

Indoor/Outdoor Wet Location Enclosure

Auto Shut Down & Reset Overload Protection

Reliable Power Source for LED Lighting Applications

Magnetic Dimmer Ready


36 Month Limited Warranty



Driver Information

Multi Output Series

Height: 14.25 inches
 Depth: 4.437 inches
 Width: 8.437 inches
 Weight: 40 lbs




All Drivers available with 120VAC or 277VAC Input options and 12VDC or 24VDC Output options.

Approvals UL1310 Listed, Class2 Power Supplies, UL1310, UL48 Recognized Sign Accessories

Multi Output: C2240 Series - 12/24 VDC Outputs

Single Output Series

Height: 11.25 inches
 Depth: 3.25 inches
 Width: 3.37 inches
 Weight: 7.0 lbs



Single Output: 961 Series - 24VDC
 601 Series - 12VDC
 481 Series - 24VDC
 361 Series - 12VDC

DIMMABLE LED DRIVERS

**UL LISTED/RECOGNIZED
CLASS 2**

Model Specifications

MODEL	INPUT VAC	INPUT AMPS	HZ	OUTPUT VAC	OUTPUT INFO
12 VOLT OUTPUT					
CC2240-12DCR	120	2.2	50 / 60	12	4 / 60 WATTS
CC2240-12DCR-277	277	0.87	50 / 60	12	4 / 60 WATTS
601-12DCR	120	0.81	50 / 60	12	1 / 60 WATTS
603-12DCR-277	277	0.38	50 / 60	12	1 / 60 WATTS
361-12DCR	120	0.58	50 / 60	12	1 / 36 WATTS
363-12DCR-277	277	0.24	50 / 60	12	1 / 36 WATTS
24 VOLT OUTPUT					
CC2240-24DCR	120	2.5	50 / 60	24	3 / 96 WATTS
CC2240-24DCR-277	277	1.04	50 / 60	24	3 / 96 WATTS
961-24DCR	120	1.12	50 / 60	24	1 / 96 WATTS
963-24DCR-277	277	0.5	50 / 60	24	1 / 96 WATTS
481-24DCR	120	0.63	50 / 60	24	1 / 48 WATTS
483-24DCR-277	277	0.28	50 / 60	24	1 / 48 WATTS
120 VAC AND 277 VAC INPUT OPTIONS 12 VDC AND 24 VDC OUTPUT OPTIONS					

Ordering Options

MODEL NUMBER		NUMBER OF UNITS
	Multiple Circuit	
	Single Circuit	
	Single Circuit	
Total Units		



THE LED COMPANY

